




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>B01D 46/02</b>	<b>A1</b>	(11) International Publication Number: <b>WO 96/24430</b> (43) International Publication Date: 15 August 1996 (15.08.96)
(21) International Application Number: PCT/SE96/00160 (22) International Filing Date: 8 February 1996 (08.02.96) (30) Priority Data: 9500470-1                      9 February 1995 (09.02.95)                      SE (71)(72) Applicant and Inventor: ANDERSSON, Per, Otto [SE/SE]; Askrikegatan 1, S-115 57 Stockholm (SE). (74) Agent: WALDINGER, Åke; Roslinvägen 41, S-161 55 Bromma (SE).	(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>	

(54) Title: BAG-TYPE FILTER DEVICE

## (57) Abstract

The invention relates to a filter device of tubular bag type for mounting in short inlet pipe sockets (11) to ventilation ducts (10). In order to obtain a filter with a sufficiently effective length this is, according to the invention, comprised of an inlet part (1) of the same length as the pipe socket (11) and at least one laterally bowed, elongated outlet part (2) with a closed end (3) extending a distance within the ventilation duct (10).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

### Bag-type Filter Device.

The present invention relates to a bag-type filter device for mounting in short inlet pipe sockets to ventilation ducts.

A filter device of this type has its limitations consisting in the facts that either the length of the filter device is restricted to the length of the pipe socket or the length of the pipe socket has to be increased such that a filter device of requisite length can be mounted in the pipe socket. A solution of the problem usually consists in a replacement of the pipe socket or a part of it by a box containing a filter device taking up a great deal of space, for instance a box containing a number of parallel bag-type filters. If there is no space for a lengthening of the pipe socket or a lateral enlargement of this by arranging a filter box, there is in broad outline only one solution left of the problem to achieve the necessary filter action, viz. arranging openings in the side walls of the ventilation ducts and the openings closing, detachable, tightly fitting doors, through which openings bag filters provided with sleeves are laterally insertable to be mounted firmly by the sleeves to retainer means attached to the inside walls of the ducts after which the doors together with sealing means have to be mounted as shown e.g. in the SE 8200764-2.

All the solutions are unpractical or cumbersome. The object of the invention is to achieve a solution of the mentioned problem in which the above mentioned drawbacks are eliminated.

This is achieved according to the invention in that an open ended inlet part of the bag-type filter device is provided with a device for sealingly attaching a portion of said openended inlet part of the filter device to the wall of said pipe socket and has an extension corresponding to the length of said pipe socket and is shaped with an extension in the shape of at least one laterally curved, elongated outlet part with a closed end. In this way it is possible to position a portion or preferably the major portion of the filter device to the ventilation ducts where it always is plenty of space for filters, but where it up to now, has been difficult to place filter devices. To insert a profiled filter through a pipe

socket and fasten the open end of the filter to the opening of the pipe socket, however, is very easy. The fastening can be performed to a reducing socket at the opening of the pipe socket or directly to the end of the pipe socket by stretching and folding the open end portion of the filter around the edges of the pipe socket and locking in a suitable way, e.g. by a mounting belt.

The invention is described more in detail in the following with reference to the attached drawing, schematically showing some embodiments of filter devices according to the invention showing in Figure 1 a perspective view of a filter device according to a first embodiment, Figure 2 is a plan view of the filter in a ventilation duct shown in longitudinal section, Figure 3 is a perspective view of the filter device according to another embodiment, Figure 4 is a plan view of the filter in Fig.3 in a ventilation duct shown in longitudinal section, and Figure 5 is a perspective view of a filter device according to a third embodiment.

The embodiment of the filter device shown in Fig.1 is made of a comparatively thick-walled filter material and is shaped like an L with a tubular inlet part 1 changing to a lateral outlet part 2 and with a closed end part 3 of filter material.

As shown in Fig.2 the filter device is intended for insertion into the ventilation duct 10 having an end portion provided with a short pipe socket 11. The diameter of the filter device 1,2,3 is a bit less than the diameter of the ventilation duct 10 and the pipe socket 11, and the open end part 4 of the inlet part 1 of the filter is in a suitable way sealingly attached to the end of a reducing socket 12, e.g. by being folded around the end of the reducing socket 12 and attached by a mounting belt 5.

The filter device 1,2,3 acts as a throttling means in the ventilation duct 10 and the pipe socket 11 when air is sucked into the ventilation duct, and by the pressure drop over the walls of the filter the tubular walls 1,2 of the filter will be sucked into and centered in the position shown in Fig.2 in the ventilation duct 10 and the pipe socket 11. A lattice gate (not shown) may be positioned over the opening 4 in the usual way.

The filter device may also have the shape shown in Fig.3 comprising an inlet part 1 and two opposite, lateral outlet parts 2 with closed ends 4. Such a filter device is intended for insertion

into a ventilation duct 10 with a lateral inlet pipe socket 11, as shown in Fig.4. If the filter material at least at the open end part 4 of the inlet part 1 is elastic it may be folded back over the end part of the pipe socket 11 and secured by a mounting belt. As an alternative the open end part 4 of the inlet part 1 may be provided with a sleeve with an enlarged part fitting the end part of the pipe socket.

An inlet pipe socket may be positioned at other locations along a ventilation duct, e.g. at an elbow. In that case the filter device will have the shape shown in Fig.5 with an inlet part 1 and two outlet parts 2 with closed ends 3 and mutually forming an angle. Also a third outlet part with a closed end is possible forming an extension of the outlet parts 2 shown in Fig.5 if the filter device is intended for insertion into a corresponding edge portion of a ventilation duct system.

The invention is of course not limited to the embodiments shown and described here, but can be modified in different ways within the scope of the inventive idea defined by the claims. This is valid a.o. in case of special designs of the ventilation ducts in which case shape and diameters or areas of inlet and outlet parts of the filter devices must be adapted to shape and diameters or areas of ventilation ducts as well as pipe sockets.

## C L A I M S

1. A filter device of tubular bag type for mounting within short inlet pipe sockets (11) to ventilation ducts (10), **characterized** in that an open ended inlet part (1) of the filter device is provided with a means for sealingly attaching a portion (4) of said open ended inlet part (1) to the wall of said pipe socket and has an extension corresponding to the length of said pipe socket and is shaped with an extension in the shape of at least one laterally curved, elongated outlet part (2) with closed end (3).

2. A filter device as claimed in claim 1, **characterized** in that the filter device has a less diameter than the ventilation ducts (10) and the pipe socket (11) and with the open ended part (4) is mounted connected to a reducing socket (12), which is attached to the end part of the inlet pipe socket (11).

3. A filter device as claimed in claim 1, **characterized** in that the filter device has a less diameter than the ventilation ducts (10) and the pipe socket (11) and consists of extensible material, the open end portion (4) of which is extensible for attaching to the wall of the pipe socket (11), preferably by folding back over the end portion of the pipe socket.

4. A filter device as claimed in any of claims 1-3, **characterized** in that the inlet part (1) of the filter device is provided with a an extension comprising two in opposite directions bowed, elongated outlet parts (2) with closed ends (3).

1 / 1

Fig. 1




Fig. 2




Fig. 3




Fig. 5





Fig. 4



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 96/00160

## A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B01D 46/02

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	SE 434466 B (KEMFILTER I SÖDERHAMN AB), 30 July 1984 (30.07.84), page 1, line 20 - line 39; page 2, line 1 - line 4, figures 3,4, claim 1, abstract  ----- --	1-4

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

29 May 1996

Date of mailing of the international search report

30 -05- 1996

Name and mailing address of the ISA  
 Swedish Patent Office  
 Box 5055, S-102 42 STOCKHOLM  
 Facsimile No. +46 8 666 02 86

Authorized officer

Tommy Vikholm  
 Telephone No. +46 8 782 25 00



### Information on patent family members

01/04/96

PCT/SE 96/00160

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
SE-B- 434466	30/07/84	SE-A- 8200764	11/08/83
-----			